UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/597,822	08/09/2006	Martin J. Edwards	14509-0131US1 / P080487SE	6742
26161 FISH & RICHA	7590 06/23/201 ARDSON PC	EXAMINER		
P.O. BOX 1022			MA, CALVIN	
MINNEAPOLIS, MN 55440-1022			ART UNIT	PAPER NUMBER
			2629	
			NOTIFICATION DATE	DELIVERY MODE
			06/23/2010	ELECTRONIC

# Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Notice of the Office communication was sent electronically on above-indicated "Notification Date" to the following e-mail address(es):

PATDOCTC@fr.com

	Application No.	Applicant(s)			
	10/597,822	EDWARDS, MARTIN J.			
Office Action Summary	Examiner	Art Unit			
	CALVIN C. MA	2629			
The MAILING DATE of this communication ap Period for Reply	ppears on the cover sheet wit	h the correspondence address			
A SHORTENED STATUTORY PERIOD FOR REP	I V IS SET TO EXDIDE 2 MG	ONTH(S) OR THIRTY (30) DAVS			
WHICHEVER IS LONGER, FROM THE MAILING I  - Extensions of time may be available under the provisions of 37 CFR 1 after SIX (6) MONTHS from the mailing date of this communication.  - If NO period for reply is specified above, the maximum statutory period - Failure to reply within the set or extended period for reply will, by statu Any reply received by the Office later than three months after the maili earned patent term adjustment. See 37 CFR 1.704(b).	DATE OF THIS COMMUNIC .136(a). In no event, however, may a red d will apply and will expire SIX (6) MONI tte, cause the application to become ABA	CATION.  ply be timely filed  THS from the mailing date of this communication.  ANDONED (35 U.S.C. § 133).			
Status					
1)⊠ Responsive to communication(s) filed on <u>25</u>	<u>March 2010</u> .				
2a) This action is <b>FINAL</b> . 2b) ☑ Th	is action is non-final.				
3) Since this application is in condition for allow	ance except for formal matte	ers, prosecution as to the merits is			
closed in accordance with the practice under	Ex parte Quayle, 1935 C.D.	11, 453 O.G. 213.			
Disposition of Claims					
4)⊠ Claim(s) <u>1-29</u> is/are pending in the applicatio	n.				
4a) Of the above claim(s) is/are withdra	awn from consideration.				
5) Claim(s) is/are allowed.					
6)⊠ Claim(s) <u>1-29</u> is/are rejected.					
7) Claim(s) is/are objected to.					
8) Claim(s) are subject to restriction and/	or election requirement.				
Application Papers					
9)☐ The specification is objected to by the Examir	ner.				
10)☐ The drawing(s) filed on is/are: a)☐ ac	ccepted or b) objected to b	y the Examiner.			
Applicant may not request that any objection to the					
Replacement drawing sheet(s) including the corre					
11) The oath or declaration is objected to by the E	Examiner. Note the attached	Office Action or form PTO-152.			
Priority under 35 U.S.C. § 119					
12) Acknowledgment is made of a claim for foreig a) All b) Some * c) None of:	n priority under 35 U.S.C. §	119(a)-(d) or (f).			
1. Certified copies of the priority documents have been received.					
2. Certified copies of the priority documer	nts have been received in Ap	oplication No			
<ol><li>Copies of the certified copies of the pri</li></ol>	ority documents have been	received in this National Stage			
application from the International Bure					
* See the attached detailed Office action for a lis	st of the certified copies not r	received.			
Attachment(s)		(DTO 440)			
Notice of References Cited (PTO-892)     Notice of Draftsperson's Patent Drawing Review (PTO-948)	Paper No(s	ummary (PTO-413) )/Mail Date			
3) Information Disclosure Statement(s) (PTO/SB/08) Paper No(s)/Mail Date	5)  Notice of In 6)  Other:	formal Patent Application _·			

Application/Control Number: 10/597,822 Page 2

Art Unit: 2629

#### **DETAILED ACTION**

### Claim Rejections - 35 USC § 103

- 1. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
  - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 2. Claims 1-5, 9, 11-14, 16-18, and 21-26 are rejected under 35 U.S.C. 103(a) as being unpatentable over Edward et al. (US Pub: 2002/0054005) in view of Herrmann (US Patent: 7,595,782).

As to claim 1, Edward teaches an active matrix display (i.e. the TFT LCD) device comprising a row and column array of picture elements (see Fig. 1),

sets of row and column address conductors for selecting rows of picture elements and providing data signals to the picture elements of a selected row respectively (i.e. the column and row electrode that lead to the individual LC pixel) (see Fig. 1),

drive means for supplying selection signals and multi-bit digital data signals respectively to the set of row address conductors and the set of column address conductors (see Fig. 1, elements 21, 23, and 25), and

in which the multi-bit digital data signals supplied to the column address conductors are converted into analogue voltage levels for use by the picture elements

by a plurality of serial charge redistribution digital to analogue conversion means (see Fig. 3, [0023-0024]),

each conversion means comprising at least first and second capacitances interconnectable by at least one conversion switch and between which charge is shared (see Fig. 3), and

in which the first and second capacitances of a conversion means are provided by the capacitances of two column address conductors (see Fig. 7, 19a, 19b),

However, Edward is silent the drive means is arranged to alternate the supply of data signals to the first and second column address conductors.

Herrmann teaches to alternate the supply of data signals to the first and second column address conductor (i.e. As seen in the drawing of figure 4 and 5 Herrmann teaches the alternating control of the row of information which is the storage of data signals that is than alternatively supplied to the pixels of first and second column of electrode as seen in figure 5a) (see Figs. 5A, 5B, 6, Col. 4, Lines 17-39).

Therefore it would have been obvious for one of ordinary skill in the art at the time the invention was made to have used the alternating data line design of Herrmann in the Edward's LCD system (i.e. having the dual or multiple column controlling switch C 31 to have the ability to allow the circuits to alternate polarity data to the circuitry) in order to reduce the cost of manufacturing and improve reliability (see Herrmann Col. 1, Lines 61-65).

As to claim 12 and 17, see claim 1 above, claim 12 and 17 are analyzed by the examiner as having broader scope as claim 1 and are rejected on the same ground.

As to claim 2, Edward teaches a device according to Claim 1, wherein the column address conductor of a conversion means to which the data signals are applied is changed after one or more complete multi-bit signal conversions performed by the conversion means (see [0028]).

As to claim 3, Edward teaches a device according to Claim 1, wherein the supply of data signals to the column address conductors of each conversion means is controlled by a switch arrangement (i.e. the switch a and b controls the supply to each column conductor) (see Fig. 7).

As to claim 4, Edward teaches a device according to Claim 3, wherein the switch arrangements of all conversion means are operable together by the drive means (i.e. the switch arrangement for the conversion means all work together to drive the display) (see [0021]).

As to claim 5, Edward teaches a device according to Claim 3, wherein the switch arrangement comprises a respective switch device connected between a column address conductor and a serial digital data signal output of the drive means (i.e. the switch a and b are between a column address conductor and a serial digital data signal

output).

As to claims 9 and 16, Edward teaches a device, wherein the picture elements comprise liquid crystal display elements (see Col. 2, Lines 10-20).

Page 5

As to claims 11 and 13, Edward and Herrmann teaches the device in which during one mode of operation of the display device, when data signals are supplied from the drive means to the first column address conductor, the data signals are not supplied to the second column address conductor, and when data signals are supplied from the drive means to the second column address conductor, the data signals are not supplied to the first column address conductor (i.e. the double data driving alternating circuitry design ensures that the two data signal applied are not redundantly applied) (see Fig. 6 of Herrmann).

As to claim 14, Edward and Herrmann teaches the device of claim 12 in which during a first period, the controller controls the switches to cause a first multi-bit digital data signal to be sent from the column driver to a first column conductor of each pair of column conductors, and causes redistribution of charges between the two column conductors of each pair of column conductors to convert the first multi-bit digital data signal to a first analog signal, and during a second period of time, the controller controls the switches to cause a second multi-bit digital data signal to be sent from the column

Art Unit: 2629

driver to a second column conductor of each pair of column conductors, and causes redistribution of charges between the two column conductors of each pair of column conductors to convert the second multi-bit digital data signal to a second analog signal (i.e. in the Edward's system the first and second column are charged by the capacitor at different time, this combined with alternating column driving design of Herrmann which would mean that the first and second period of time of the conversion would be applied to the different columns driven by the different sub-driver) (see Edward Fig. 3).

As to claim 18, see claim 6 above, claim 18 is analyzed to be of the same scope as claim 6 and is rejected for the same reason.

As to claims 21, 23, and 26, Edward and Herrmann teaches the device in which the drive means comprises a digital data output that is arranged to alternate the supply of data signals to the first and second column address conductors of each conversion means (i.e. As seen in the drawing of figure 4 and 5 Herrmann teaches the alternating control of the row of information which is the storage of data signals that is than alternatively supplied to the pixels of first and second column of electrode as seen in figure 5a)(see Herrmann Fig. 6, Col. 4, Lines 20-50, Edward Fig. 3).

As to claim 22, 24, and 26, Edward and Herrmann teaches the device in which the drive means is arranged to alternate in time the supply of data signals to the first

and second column address conductors (see Herrmann Fig. 6, Col. 4, Lines 20-50, Edward Fig. 3).

.

3. Claims 6-8, 10, 15 and 19-20 are rejected under 35 U.S.C. 103(a) as being unpatentable over Edward in view of Herrmann as applied to claim 1-5, 9 and 11-14, 16-18 above, and further in view of Janssen et al. (US Patent: 6469687).

As to claims 6 and 15, Edward and Herrmann teaches a device of claim one but does not teach wherein the polarity of the voltage provided to the picture elements is inverted periodically, and wherein the alternation of the column conductors of a conversion means to which a data signal is applied to generate the analogue voltage level for a given picture element is synchronized with the inversion of the picture element voltage.

Janssen teaches the polarity of the voltage provided to the picture elements is inverted periodically, and wherein the alternation of the column conductors of a conversion means to which a data signal is applied to generate the analogue voltage level for a given picture element is synchronized with the inversion of the picture element voltage (see Janssen Col. 2, Lines 4-7).

Therefore it would have been obvious for one of ordinary skill in the art at the time the invention was made to have modified the system of Edward and Herrmann with the method of Janssen whereby the data signal that is applied is changed every second time the polarity of the picture element is inverted, thus reducing or eliminating sampling

As to claims 7 and 19, Edward, Herrmann and Jannsen teaches a device, wherein the drive means and the conversion means are operable such that for a given picture element the column address conductor of its associated conversion means to which a data signal is applied is changed each time the polarity of the picture element voltage is inverted (i.e. the sequential driving of the TFT circuitry of Herrmann clearly shows the inverting nature of the LCD driving structures whereby the active matrix display is driven in an AC mode to ensure stable driving conditions ) (see Fig. 8 of Herrmann).

As to claims 8 and 20, Edward and Herrmann teaches a device, wherein the drive means and the conversion means are operable such that for a given picture element the column address conductor of its associated conversion means.

However Edward and Herrmann does not explicitly teach means to which a data signal is applied is changed every second time the polarity of the picture element is inverted. Janssen teaches the data signal that is applied is changed every second time the polarity of the picture elements is inverted (see Janssen Col. 2, Lines 4-7).

Therefore it would have been obvious for one of ordinary skill in the art at the time the invention was made to have modified the system of Edward and Herrmann with the method of Janssen whereby the data signal that is applied is changed every second time the polarity of the picture element is inverted, thus reducing or eliminating sampling

Art Unit: 2629

errors (see Janssen Col. 2, Lines 4-7).

As to claim 10, Janssen teaches a device according to Claim 9, wherein the drive means is arranged to alternate the supply of data to the first and second column address conductors with a period which is shorter than the response time of the liquid crystal material (see Janssen Col. 6, Lines 10-23).

### Response to Arguments

4. Applicant's arguments with respect to claims 1-20 have been considered but are moot in view of the new ground(s) of rejection.

## Inquiry

Any inquiry concerning this communication or earlier communications from the examiner should be directed to CALVIN C. MA whose telephone number is (571)270-1713. The examiner can normally be reached on 7:30-5:00.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Chanh Nguyen can be reached on 571-272-7772. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Application/Control Number: 10/597,822 Page 10

Art Unit: 2629

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

Calvin Ma June 4, 2010 /Chanh Nguyen/ Supervisory Patent Examiner, Art Unit 2629